



---

## LDG-M4 Compact Housing



---

[www.erni.com](http://www.erni.com)



The LDG-M4 is a plastic housing designed for industrial applications in the field of sensors. The dimensions are according to DIN EN 50041.

The waterproof housing can i.e. be used to protect proximity- or positioning switches or other electronic circuits.

The cable is fed through into the housing by a cable gland size M20 x 1.5.

On request the housing can be supplied in customer specific colors. Furthermore it is possible to create cut outs into the top or the housing for additional cable glands, connectors, LEDs, pressure sensors, etc.

**Standard note:**

**DIN EN 50041** - Low voltage switchgear for industrial use; control switches; position switches 42.5 x 80; dimensions and characteristics

# LDG-M4 Compact Housing

## Features



Cover with recess for printed text or rating plate (max. 49 x 38 mm).  
An area of 40 x 30 mm can be used for cut outs e.g. for connectors or LED-displays.

**Note:**

The parts used have to meet IP 65/67 standards in conjunction with the housing.



Cover with water- and oil-proof seal and fixing screws.  
The use of metal thread inserts results in a robust long-life assembly (M3).



Wall mounting is enabled by 2 diagonal arranged screw holes. The mounting grid is 60 x 30 mm. The screw holes are suitable for cylinder head screw size M5 x 40 (including usable thread length of 10 mm)

PCB fixation with 2 diagonal arranged screw holes for self-tapping screws (suitable for plastic, size 2.5 , max. torque have to be noted)

In conjunction with a 1.6 mm thick pcb, a self-tapping screw 2.5 x 6 can be used.

**Technical data**

Outside dimensions	L x W x H	94 x 42 x max. 46 mm
Cable gland size		M20 x 1.5
Screw-mounting grid	DIN EN 50041	60 x 30 mm
Protection class	EN 60529	IP 65/67 complete assembled system
Assembly height Component side	PCB thickness 1.6 mm	max. 30 mm
Assembly height Solder side	PCB thickness 1.6 mm	max. 4.5 mm
Temperature range		-20 bis +70 °C

**Material**

Housing with M3 thread insert	grey RAL 7032	Makrolon 8035 30% GF UL94 V-1
Top	grey RAL 7032 transparent	Makrolon 8035 30% GF (UL94 V-1) Makrolon 2805 (UL94 V-2)
Sealing gasket		CR Neoprene
Cable gland	M20 x 1.5	Brass with Ni plating
PCB thickness	recommended	1.6 mm

**Locking Torque**

Cover screw connection M3		max. 0.4 Nm
PCB-fastening Screw size 2.5 x 6		max. 0.25 Nm
Wall fastening M5 x 40		max. 1.0 Nm





Member





**ERNI Electronics GmbH**

Seestrasse 9  
73099 Adelberg, Deutschland  
Tel +49 (0)71 66 50-0  
Fax +49 (0)71 66 50-282  
info@erni.de

Europe South America Africa Japan

**ERNI Electronics, Inc.**

3005 E. Boundary Terrace  
Midlothian, VA 23112  
Tel +1 (804) 228-4100  
Fax +1 (804) 228-4099  
info.usa@erni.com

North America Canada Mexico

**ERNI Asia Holding Pte Ltd.**

Blk 4008 Ang Mo Kio Avenue 10  
#04-01/02 Techplace I  
Singapore 569625  
Tel +65 6 555 5885  
Fax +65 6 555 5995  
info@erni-asia.com

Asia

[www.erni.com](http://www.erni.com)

© ERNI Electronics GmbH 2008 • Printed in Germany. A policy of continuous improvement is followed and the right to alter any published data without notice is reserved.  
ERNI®, MicroStac®, MicroSpeed®, MiniBridge®, MaxiBridge®, ERmet®, ERmet ZD®, ERbic® and ERNIPRESS® are trademarks (registered or applied for in various countries) of ERNI Electronics GmbH.